

## Preassembled cables. MTP Elite - MTP Elite, E9/125 G.657.A2 OS2



image similar

### Description

Compact, metal-free cable construction with FR/LSOH cable sheath and 12 to 144 fibres.  
 The length of individual cables ("legs") may be defined on the basis of a specific project.  
 All individual cables are assembled using MTP connectors with high-performance 12-fibre Elite® ferrules (LCD connectors available on request).  
 Polarisation modes can be type A, type B or type C.  
 The preassembled cables guarantee high reliability based on 100% performance test and quality inspection in the factory.  
 The cables come with an effective protection for cable and connector.  
 Quick and easy installation on site.  
 Rodent protection optional.

### Impresión de aplicaciones

Campus and backbone cabling  
 Industrial plant cabling  
 Fibre optic cabling in data centres  
 nur China

### Construcción

Color de la funda exterior	amarillo
Material exterior de la vaina	LSZH

### Propiedades ópticas

Conector de pulido de férulas A	Elite APC 8°
Conector de pulido de férulas B	Elite APC 8°
IL máximo, conector A	0,3 dB
IL máximo, conector B	0,3 dB
RL minimal, conector A	55 dB
RL minimal, conector B	55 dB
Tipo de fibra	E9/125 G.657.A2 OS2

## Forma de suministro

Preassembled cable, packed in recyclable cardboard drum or box  
Installation guide enclosed  
Comes with test protocol

## Estándares

Cero halógeno gases no corrosivos	IEC 60754-1/-2
Dispersión de llamas	IEC 60332-3-24
Densidad de humo	IEC 61034-1/-2

## Nota

MTP® and MTP Elite® are registered brands of US Conec.

## Versións

Número de material	Producto	Color de la funda exterior	Longitud (m)	Peso [kg]
4122435	Preassembled cables MTP Elite - MTP Elite	amarillo	1	0,01 kg
4122441	Preassembled cables MTP Elite - MTP Elite	amarillo	1	0,01 kg
4122417	Preassembled cables MTP Elite - MTP Elite	amarillo	1	0,01 kg
4122436	Preassembled cables MTP Elite - MTP Elite	amarillo	1	0,01 kg
4122442	Preassembled cables MTP Elite - MTP Elite	amarillo	1	0,01 kg

Other lengths and versions on request.