

Preassembled cables. MTP Elite - MTP Elite, E9/125 G.657.A2 OS2



image similar

Description

Compact, metal-free cable construction with FR/LSOH cable sheath and 12 to 144 fibres. The length of individual cables ("legs") may be defined on the basis of a specific project. All individual cables are assembled using MTP connectors with high-performance 12-fibre Elite® ferrules (LCD connectors available on request).
Polarisation modes can be type A, type B or type C.
The preassembled cables guarantee high reliability based on 100% performance test and quality inspection in the factory. The cables come with an effective protection for cable and connector.
Quick and easy installation on site.
Rodent protection optional.

Applicazione

Campus and backbone cabling
Industrial plant cabling
Fibre optic cabling in data centres

Costruzione

Outer sheath colour	giallo
Outer sheath material	LSZH

Proprietà ottiche

Connettore per lucidatura della ghiera A	Elite APC 8°
Connettore per lucidatura della ghiera B	Elite APC 8°
IL maximal, connettore A	0,3 dB
IL maximal, connettore B	0,3 dB
RL minimal, connector A	55 dB
RL minimal, connector B	55 dB
Tipologia di fibra	E9/125 G.657.A2 OS2

Scope of delivery

Preassembled cable, packed in recyclable cardboard drum or box
Installation guide enclosed
Comes with test protocol

Standards

Zero halogen no corrosive gases	IEC 60754-1/-2
Flame Spread	IEC 60332-3-24
Smoke Density	IEC 61034-1/-2

Nota

MTP® and MTP Elite® are registered brands of US Conec.

Versions

Numero Materiale	Product	Outer sheath colour	Length (m)	Peso [kg]
4122435	Preassembled cables MTP Elite - MTP Elite	giallo	1	0,01 kg
4122441	Preassembled cables MTP Elite - MTP Elite	giallo	1	0,01 kg
4122417	Preassembled cables MTP Elite - MTP Elite	giallo	1	0,01 kg
4122436	Preassembled cables MTP Elite - MTP Elite	giallo	1	0,01 kg
4122442	Preassembled cables MTP Elite - MTP Elite	giallo	1	0,01 kg

Other lengths and versions on request.

Con riserva di modifiche tecniche

A partire da 2021-01-27 11:42:00