

FE5-CL

Safety cable, 0.6/1kV, armoured with rodent protection, euroclass B2ca

halogen-free, with improved fire characteristics,

with reference to SEV TP 20B/3C and CENELEC HD 604 S1 part 5. H



- 1 Conductor: solid/stranded
- 2 Insulation: cross-linked PE, zero halogen
- 3 Inner sheath: Polyolefin, flame retardant, zero halogen
- 4 Armouring: galvanised steel tape
- 5 Sheath: FRNC/LSZH



Description

For permanent installation in dry, damp or wet areas, on or behind plasterwork or in walls or concrete. Also suitable for outdoor applications.

The cable should only be laid directly in earth or water if a protective conduit is used.

Permitted operating temperature at conductor of +90°C.

Construction

Armouring (rodent protection)	Single-core cable with copper tape (CLCU) and multicore cable with galvanised steel tape (CL)
Conductor	Bare copper, solid or stranded in accordance with IEC 60228 and EN 60228
Core colours	CENELEC HD 308 S2
Insulation	Cross-linked Polyethylene CENELEC HD 604 S1 part 5 sec. H
Outer sheath material	Flame retardant Polyolefin compound CENELEC HD 604 S1 part 5 sec. H

General Properties

Installation temperature	-5 °C - +50 °C
Operating temperature	-45 °C - +90 °C

Mechanical properties

Minimum bending during installation (multi core)	12 x D
Minimum bending during installation (single core)	15 x D
Minimum bending radius permanent (multi core)	12 x D
Minimum bending radius permanent (single core)	15 x D

Standards

Reaction to fire (Euroclasses)	EN 13501-6
Zero halogen no corrosive gases	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2, AREI-RGIE Art.104-SA
Flame Propagation	IEC 60332-1-2, EN 60332-1-2, VDE 0482-332-1-2, AREI-RGIE Art.104-F1
Flame Spread	IEC 60332-3-24, EN 60332-3-24, AREI-RGIE Art.104-F2
Smoke Density	IEC 61034-1/-2, EN 61034-1/-2, VDE 0482-1034-1/-2, AREI-RGIE Art.104-SD

Note

Additional dimensions available on request.

Versions

Material number	Product	Reaction To Fire	Diameter mm ²	Outer sheath diameter [mm]	CU rate [kg/km]	Weight [kg/km]	Fire load [kWh/m]	Conductor	Construction	Packing unit
19586400BZ	FES-CL-O 2 x 2.5	B2ca-s1a,d1,a1	2.5	10	49	153	0.37	solid	LN	by the metre
19273000BZ	FES-CL-J 3 x 2.5	B2ca-s1a,d1,a1	2.5	10	72	170	0.41	solid	LNPE	by the metre
19109100BZ	FES-CL-J 3 x 4	B2ca-s1a,d1,a1	4	11	115	238	0.48	solid	LNPE	by the metre
19164500BZ	FES-CL-J 3 x 6	B2ca-s1a,d1,a1	6	13	173	333	0.65	solid	LNPE	by the metre
19156800BZ	FES-CL-J 3 x 10	B2ca-s1a,d1,a1	10	16	288	505	0.91	solid	LNPE	by the metre
19167200BZ	FES-CL-J 4 x 1.5	B2ca-s1a,d1,a1	1.5	9	58	153	0.36	solid	3LPE	by the metre
19626400BZ	FES-CL-J 5 x 1.5	B2ca-s1a,d1,a1	1.5	10	72	176	0.45	solid	3LNPE	by the metre
19106400BZ	FES-CL-J 5 x 2.5	B2ca-s1a,d1,a1	2.5	12	120	264	0.59	solid	3LNPE	by the metre
19273100BZ	FES-CL-J 5 x 4	B2ca-s1a,d1,a1	4	14	192	364	0.73	solid	3LNPE	by the metre
19059500BZ	FES-CL-J 5 x 6	B2ca-s1a,d1,a1	6	16	288	497	0.92	solid	3LNPE	by the metre
18838900BZ	FES-CL-J 5 x 10	B2ca-s1a,d1,a1	10	18	480	743	1.56	solid	3LNPE	by the metre
19040100BZ	FES-CL-J 5 x 16	B2ca-s1a,d1,a1	16	24	768	1,120	2.03	stranded	3LNPE	by the metre
19106300BZ	FES-CL-J 5 x 25	B2ca-s1a,d1,a1	25	28	1,200	1,710	2.76	stranded	3LNPE	by the metre
19109000BZ	FES-CL-J 5 x 35	B2ca-s1a,d1,a1	35	31.8	1,680	2,277	3.44	stranded	3LNPE	by the metre
19103600BZ	FES-CL-J 5 x 50	B2ca-s1a,d1,a1	50	36	2,400	3,144	4.74	stranded	3LNPE	by the metre
19160000BZ	FES-CL-J 5 x 95	B2ca-s1a,d1,a1	95	49	4,560	5,854	8.16	stranded	3LNPE	by the metre
18092900BZ	FES-CL-J 7 x 6	B2ca-s1a,d1,a1	6	17	403	633	1.1	solid	6LPE	by the metre
18453100BZ	FES-CL-J 7 x 10	B2ca-s1a,d1,a1	10	20	672	964	1.48	solid	6LPE	by the metre