

FO-DCS 3U/7HP BO plug-in-modules, 6x LSH-C

for FO-DCS modular subracks / panels

for OM3, OM4, OS2



High-Performance FO-DCS BO plug-in modules LSH-C, 3U/7HP

Description

Open polycarbonate housing (PC) and front panel 3U / 7HP in polycarbonate (black).
The radius limiter on the rear side and the integrated clips ensure a simple and safe handling of the pre-assembled legs.
The front panel is fitted with 6 LSH-C adapters and provides two integrated labelling strips for customer-specific printing.
Fixation with two knurled screws (captive).

Application

FO-DCS breakout plug-in modules LSH-C (12F 3U/7HP) are suitable for all high-performance applications with duplex signals, particularly in the data centre environment.

They find modular application in FO-DCS modular panels (19"/1U) or in FO-DCS subracks (19"/3U, 19"/4U).

They are used to accept pre-assembled LC/LCD trunk cables.

Packing densities of up to 144 fibres on 3U are achieved with these plug-in modules.

General Properties

Acceptance capacity	6 duplex ports (12 fibres)
Fully equipped	Yes

Optical Properties

Adapter colour, front side	green
Adapter material, front side	Polymeric
Adapter type, front side	LSH-C/APC

Scope of delivery

Housing with front panel, equipped with 6 LSH-C adapters (ceramic sleeves).

All ports are fitted with two transparent dust protection plugs (front/rear).

Rear side with integrated radius limiter and clips for the pre-assembled legs.

Versions

Material number	Product	Outer dimensions (HxWxD)	Colour	Material	Weight [kg]	Packing unit
57157500ZY	FO-DCS BO plug-in-module LCD 3U/7HP, 6x LSH-C/APC, green	3 U, 129 mm x 35 mm x 188 mm	black	Polycarbonate (PC)	0.3 kg	1 pc.