


## KU CC219 Cat.5e, Cat.6 and Cat.6<sub>A</sub>

RJ45 modules, unshielded, 180°



CC219 series RJ45 module, unshielded, Cat.6<sub>A</sub>, white

### Beschreibung

Compact design, helps to improve the NEXT, suitable for high density cabling systems.  
 Housing made of high-impact resistant, flame retardant compound, UL94V-0 rated, with Keystone mounting clip.  
 Arc cross design for the lead frame, enhances transmission performance.  
 Suitable for 4PPoE.  
 Contact spring with phosphor bronze alloy, plated with gold.  
 IDC made of phosphor bronze alloy.  
 Meet RoHS requirements.

### Anwendung

For the transmission of digital and analogue voice, video and data signals.  
 Suitable for Class D/E/E<sub>A</sub> channel application in accordance with ISO/IEC 11801, EN 50173 and ANSI/TIA-568-C.2.

### Allgemeine Eigenschaften

Betriebstemperatur	-10 °C - +60 °C
Installationstemperatur	-10 °C - +60 °C
Lagertemperatur	-40 °C - +70 °C

### Elektrische Eigenschaften

Maximaler DC-Nennstrom	1,5 A
Maximaler Kontaktwiderstand	20 mΩ
Minimaler Isolationswiderstand	1.000 MΩ

### Mechanische Eigenschaften

Verbindungs Typ	IDC insulation displacement connectors
Cu-Leiter Draht	0.40 (AWG26) - 0.57 (AWG23)
Wiederbeschaltbar	≥ 200 cycles
Minimale Anzahl Steckzyklen	1.500

### Normen

Steckerstandard	IEC 60603-7-4, IEC 60603-7-2
Verkabelungsnormen	TIA-568-C.2, EN 50173-1, GB 50311, ISO/IEC 11801-1

### Anmerkung

Modules fit in all Datwyler Keystone patch panels and faceplates (ISO/IEC 60603-7)

### Versionen

Artikelnummer	Produkt	Farbe	Kategorie	Physische Bandbreite [MHz]	Gewicht [kg]	Verpackungseinheit
4109369	KU CC219 RJ45 module, unshielded	weiß	Cat.5e	100	0,01 kg	1 Stk.
4109821	KU CC219 RJ45 module, unshielded	blau	Cat.5e	100	0,01 kg	1 Stk.
4109822	KU CC219 RJ45 module, unshielded	gelb	Cat.5e	100	0,01 kg	1 Stk.
4109823	KU CC219 RJ45 module, unshielded	rot	Cat.5e	100	0,01 kg	1 Stk.
4109819	KU CC219 RJ45 module, unshielded	weiß	Cat.6	250	0,01 kg	1 Stk.
4109824	KU CC219 RJ45 module, unshielded	blau	Cat.6	250	0,01 kg	1 Stk.
4109825	KU CC219 RJ45 module, unshielded	gelb	Cat.6	250	0,01 kg	1 Stk.
4109826	KU CC219 RJ45 module, unshielded	rot	Cat.6	250	0,01 kg	1 Stk.
4109827	KU CC219 RJ45 module, unshielded	schwarz	Cat.6	250	0,01 kg	1 Stk.
4109828	KU CC219 RJ45 module, unshielded	grün	Cat.6	250	0,01 kg	1 Stk.
4109820	KU CC219 RJ45 module, unshielded	weiß	Cat.6 <sub>A</sub>	500	0,01 kg	1 Stk.