

KU CC219 Cat.5e, Cat.6 and Cat.6_A

RJ45 modules, unshielded, 180°



CC219 series RJ45 module, unshielded, Cat.6_A, white

Description

Compact design, helps to improve the NEXT, suitable for high density cabling systems.
 Housing made of high-impact resistant, flame retardant compound, UL94V-0 rated, with Keystone mounting clip.
 Arc cross design for the lead frame, enhances transmission performance.
 Suitable for 4PPoE.
 Contact spring with phosphor bronze alloy, plated with gold.
 IDC made of phosphor bronze alloy.
 Meet RoHS requirements.

Impresión de aplicaciones

only available in china
 For the transmission of digital and analogue voice, video and data signals.
 Suitable for Class D/E/E_A channel application in accordance with ISO/IEC 11801, EN 50173 and ANSI/TIA-568-C.2.

Propiedades generales

Temperatura de almacenamiento	-40 °C - +70 °C
Temperatura de funcionamiento	-10 °C - +60 °C
Temperatura de instalación	-10 °C - +60 °C

Propiedades eléctricas

Maximum contact resistance	20 mΩ
Maximum DC current rating	1,5 A
resistencia mínima de aislamiento	1.000 MΩ

Propiedades mecánicas

Tipo de conexión	IDC insulation displacement connectors
Alambre de cobre sólido	0.40 (AWG26) - 0.57 (AWG23)
Reutilizable	≥ 200 cycles
Minimum insertion lifetime	1.500

Estándares

Connector standards	IEC 60603-7-4, IEC 60603-7-2
Estándares de cableado	TIA-568-C.2, GB 50311, EN 50173-1, ISO/IEC 11801-1

Nota

Modules fit in all Datwyler Keystone patch panels and faceplates (ISO/IEC 60603-7)

Versions

Número de material	Producto	Color	Category	Physical bandwidth [MHz]	Peso [kg]	Unidad de embalaje
4109369	KU CC219 RJ45 module, unshielded	blanco	Cat.5e	100	0,01 kg	1 pza.
4109821	KU CC219 RJ45 module, unshielded	azul	Cat.5e	100	0,01 kg	1 pza.
4109822	KU CC219 RJ45 module, unshielded	amarillo	Cat.5e	100	0,01 kg	1 pza.
4109823	KU CC219 RJ45 module, unshielded	tinto	Cat.5e	100	0,01 kg	1 pza.
4109819	KU CC219 RJ45 module, unshielded	blanco	Cat.6	250	0,01 kg	1 pza.
4109824	KU CC219 RJ45 module, unshielded	azul	Cat.6	250	0,01 kg	1 pza.
4109825	KU CC219 RJ45 module, unshielded	amarillo	Cat.6	250	0,01 kg	1 pza.
4109826	KU CC219 RJ45 module, unshielded	tinto	Cat.6	250	0,01 kg	1 pza.
4109827	KU CC219 RJ45 module, unshielded	negro	Cat.6	250	0,01 kg	1 pza.
4109828	KU CC219 RJ45 module, unshielded	green	Cat.6	250	0,01 kg	1 pza.
4109820	KU CC219 RJ45 module, unshielded	blanco	Cat.6 _A	500	0,01 kg	1 pza.

Sujeto a modificaciones técnicas

A partir de 2021-01-22 11:00:39