

KS CC201 Cat.5e and Cat.6

RJ45 modules, shielded, 180°



CC201 series RJ45 modules, shielded, Cat.5e and Cat.6



Description

Housing made of high impact resistant, flame retardant materials, UL94V-0 rated.
Solid zinc alloy connector housing with snap-in.
The metal shielding ensures a fully shielded environment.
Wire guides support termination in accordance with the color code T568-A and B.
RJ45 modules in accordance with IEC 60603.
Fit in all Datwyler Keystone patch panels and faceplates.

Application

For the transmission of digital and analogue voice-, video- and data signals.
Suitable for all Class D/Class E applications respectively in accordance with ISO/IEC 11801, EN 50173-1 and TIA/EIA 568-C.2.

Propriétés générales

Température d'installation	-10 °C - +60 °C
Température de fonctionnement	-20 °C - +60 °C
Température de stockage	-40 °C - +70 °C

Propriétés mécaniques

Type de connexion	Connecteurs à déplacement d'isolant IDC
Fil de cuivre solide	0.50 (AWG 26) - 0.64 (AWG 22)
Fil de cuivre toronné	AWG26/7 - AWG26/8
Diamètre sur isolation	0.70 mm - 1.40 mm

Normes

Cat./Class	Cat.5/5e / Class D
Fiche standard	IEC 60603-7-5
Normes de câblage	GB 50311, ISO/IEC 11801-1, TIA-568-C.2

Versions

Numéro de matériau	No. de produit	Produit	Couleur	Catégorie	Poids [kg]	Unité d'emballage
418051	CC201-KS51	KS CC201 Cat.5e module, shielded, 180°	metal	Cat.5e	0,02 kg	10 pcs.
418050	CC201-KS60	KS CC201 Cat.6 module, shielded, 180°	metal	Cat.6	0,02 kg	10 pcs.