

KS CC201 Cat.5e and Cat.6

RJ45 modules, shielded, 180°



CC201 series RJ45 modules, shielded, Cat.5e and Cat.6



Description

Housing made of high impact resistant, flame retardant materials, UL94V-0 rated.
 Solid zinc alloy connector housing with snap-in.
 The metal shielding ensures a fully shielded environment.
 Wire guides support termination in accordance with the color code T568-A and B.
 RJ45 modules in accordance with IEC 60603.
 Fit in all Datwyler Keystone patch panels and faceplates.

Applicazione

For the transmission of digital and analogue voice-, video- and data signals.
 Suitable for all Class D/Class E applications respectively in accordance with ISO/IEC 11801, EN 50173-1 and TIA/EIA 568-C.2.

Proprietà generali

Installation temperature	-10 °C - +60 °C
Operating temperature	-20 °C - +60 °C
Storage temperature	-40 °C - +70 °C

Proprietà meccaniche

Connection type	Connettori a perforazione di isolante IDC
Solid copper wire	0.50 (AWG 26) - 0.64 (AWG 22)
Stranded copper wire	AWG26/7 - AWG26/8
Diameter over Insulation	0.70 mm - 1.40 mm

Standards

Cat./Class	Cat.5e / Class D
Connector standards	IEC 60603-7-5
Cabling standards	ISO/IEC 11801-1, TIA-568-C.2, GB 50311

Versions

Numero Materiale	Product no.	Product	Colore	Category	Peso [kg]	Packing unit
418051	CC201-KS51	KS CC201 Cat.5e module, shielded, 180°	metal	Cat.5e	0,02 kg	10 pcs.
418050	CC201-KS60	KS CC201 Cat.6 module, shielded, 180°	metal	Cat.6	0,02 kg	10 pcs.