

## HD-DCS BO module, 12x LCD/PC, OM4

for HD-DCS modular panels



### Description

Polycarbonate (PC) housing with press-fit cover.  
 At the rear the HD-DCS BO modules have a slot fitted with a cable grommet.  
 Front couplers with integrated, automatic transparent dust shutters.

### Applicazione

HD-DCS BO modules are suitable for all high-density and high-performance applications with duplex signals, particularly in the data centre environment.  
 They find modular application in the slots of the HD-DCS modular panels (19"/1U) in which they can be inserted from the front and the back.  
 They are used to accept pre-assembled LC/LCD trunk cables.  
 A packing density of 96 fibres on 1U are achieved with these type of modules.

### Proprietà generali

Acceptance capacity	24 fibres
---------------------	-----------

### Proprietà ottiche

Adapter colour, front side	heather violet
Adapter material, front side	Polimerico
Adattatore, lato anteriore	2 x 6LCD, heather violet (Inner shutter, translucent)
Materiale manicotto, lato anteriore	Zirconia (ZrO <sub>2</sub> )
Number of adapters, front side	2
Tipo di adattatore, lato anteriore	6LCD

### Proprietà meccaniche

Dust protection, frontside	Yes
Dust/Laser protection, frontside	Inner shutter, translucent
Laser protection, frontside	No

### Scope of delivery

Housing, equipped with 2x 6LCD adapter with ceramic sleeves and translucent inner shutter on front side.  
 Rear side is fitted with a cable grommet.

### Standards

LC standard (IEC)	IEC 61754-20
-------------------	--------------

### Nota

As high-performance patch cables for high-density solutions Datwyler recommends the HD-DCS LCD Uniboot patch cables with push-pull rods.

## Versions

Numero Materiale	Product	Dimensioni esterne	Colore	Materiale	Peso [kg]	Packing unit
473540	HD-DCS BO module, 12x LCD/ PC, OM4	39 mm x 100 mm x 120 mm	nera	Polycarbonate (PC)	0,11 kg	1 pc.

Con riserva di modifiche tecniche

A partire da 2021-07-01 11:29:52