

## HD-DCS Indoor cables MTP-MTP, 12-144 fibres OS2

for interconnecting HD-DCS modules



HD-DCS Indoor cables MTP-MTP, 12-144 fibres OS2

### Description

Compact, metal-free cable construction with FR/LSOH cable sheath and 12 to 144 fibres. OS2 versions with Euroclass D<sub>ca</sub> are available (Euroclass C<sub>ca</sub> or B2<sub>ca</sub> version available on request). Sticker labelling at both cable ends. The length of individual cables ("legs") may be defined on the basis of a specific project (standard 0.55 m, max. 4.0 m). The leg separation is effected with a divider housing. All individual cables are assembled using MTP<sup>®</sup> connectors with high-performance 12-fibre Elite<sup>®</sup> ferrules (MTP<sub>8</sub>/MTP<sub>24</sub> available on request). Standard connectivity methods can be type A or type C (other types available on request). The cables are fitted at both ends with protective sleeves.

### Application

OS2 MTP-on-MTP Indoor cables are suitable for all high-performance applications with duplex and parallel optic signals in a data centre environment. They are particularly used when installation requires sturdy, metal-free indoor cables that provide enhanced crush resistance and rodent protection. For duplex applications, the pre-assembled connectors at either end of the cable are connected to the HD-DCS modules. The HD-DCS Indoor cables are assembled to a very high quality and guarantee optimum values for optical performance (IL/RL).

### Construction

Outer sheath colour	yellow
Outer sheath material	FR/LSZH

### Optical Properties

Colour code	IEC 60304
Connector gender side A	Male (pinned)
Connector gender side B	Male (pinned)
Connector type side A	MTP
Connector type side B	MTP
Ferrule polishing connector A	Elite APC 8°
Ferrule polishing connector B	Elite APC 8°
Fibre type	E9/125 G.652.D BLO
IL maximal, connector A	0.3 dB
IL maximal, connector B	0.3 dB
IL typical, connector A	0.1 dB
IL typical, connector B	0.1 dB
RL minimal, connector A	65 dB
RL minimal, connector B	65 dB
RL typical, connector A	70 dB

RL typical, connector B	70 dB
-------------------------	-------

## Mechanical properties

Housing colour connector A	yellow
Housing colour connector B	yellow

## Scope of delivery

HD-DCS Indoor cables (FR/LS0H) with 12-144 fibres OS2.  
 High-performance connector assembly at either end with MTP Elite (male).  
 Sticker labelling at both cable ends.  
 Test reports on all MTP connectors.

## Standards

MTP standard (IEC)	IEC 61754-7, IEC 61755-3-31, IEC 61755-3-32
Polarity standard	TIA-568-C.3 Type A,B,C
Zero halogen no corrosive gases	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2
Flame Propagation	IEC 60332-1-2, EN 60332-1-2, VDE 0482-332-1-2
Flame Spread	IEC 60332-3-24
Smoke Density	IEC 61034-1/-2, EN 61034-1/-2, VDE 0482-1034-1/-2

## Versions

Material number	Product	Outer sheath colour	Number of Fibres	Outer sheath diameter [mm]	Minimum bending radius	Tensile load short term [N]	Tensile load continuous [N]	Crush resistance short term [N]	Crush resistance continuous [N]
474040	HD-DCS Indoor cable 1x MTP - 1x MTP	yellow	12	5.9	120	3,000	1,000	4,000	1,200
474041	HD-DCS Indoor cable 2x MTP - 2x MTP	yellow	24	9.9	200	8,000	4,100	4,000	1,200
474042	HD-DCS Indoor cable 4x MTP - 4x MTP	yellow	48	9.9	200	8,000	4,100	4,000	1,200
474044	HD-DCS Indoor cable 8x MTP - 8x MTP	yellow	96	12.9	255	8,000	4,100	4,000	1,200
474045	HD-DCS Indoor cable 12x MTP - 12x MTP	yellow	144	15.8	320	8,000	4,100	4,000	1,200
474050	HD-DCS Indoor cable 1x MTP - 1x MTP	yellow	12	5.9	120	3,000	1,000	4,000	1,200
474051	HD-DCS Indoor cable 2x MTP - 2x MTP	yellow	24	9.9	200	8,000	4,100	4,000	1,200
474052	HD-DCS Indoor cable 4x MTP - 4x MTP	yellow	48	9.9	200	8,000	4,100	4,000	1,200
474054	HD-DCS Indoor cable 8x MTP - 8x MTP	yellow	96	12.9	255	8,000	4,100	4,000	1,200
474055	HD-DCS Indoor cable 12x MTP - 12x MTP	yellow	144	15.8	320	8,000	4,100	4,000	1,200

MTP® and MTP Elite® are registered brands of US Conec.