

HD-DCS Breakout cables MTP-MTP, 12-144 fibres OM4

for interconnecting HD-DCS modules



HD-DCS Breakout cables MTP-MTP, 12-144 fibres OM4

Description

Compact, metal-free cable construction with FR/LSOH cable sheath and 12 to 144 fibres.

OM4 versions available (Euroclass B2_{ca} on request).

Sticker labelling at both cable ends.

The length of individual cables ("legs") may be defined on the basis of a specific project (standard 0.55 m, max. 4.0 m).

All individual cables are assembled using MTP[®] connectors with high-performance 12-fibre Elite[®] ferrules (MTP₈/MTP₂₄ available on request).

Standard connectivity methods can be type A or type C (other types available on request).

The cables are fitted at both ends with protective sleeves.

Applicazione

OM4 MTP-on-MTP Breakout cables are suitable for all high-performance applications with duplex and parallel optic signals in a data centre environment.

They are particularly used when installation requires sturdy, metal-free indoor cables that provide enhanced crush resistance.

For duplex applications, the pre-assembled connectors at either end of the cable are connected to the HD-DCS modules.

The HD-DCS Breakout cables are assembled to a very high quality and guarantee optimum values for optical performance (IL/RL).

Costruzione

Outer sheath colour	heather violet
Outer sheath material	FR/LSZH

Proprietà ottiche

Codice colore	IEC 60304
Connector gender side A	Male (pinned)
Connector gender side B	Male (pinned)
Connector type side A	MTP
Connector type side B	MTP
Connettore per lucidatura della ghiera A	Elite PC 0°
Connettore per lucidatura della ghiera B	Elite PC 0°
IL maximal, connettore A	0,25 dB
IL maximal, connettore B	0,25 dB
IL tipico, connettore A	0,15 dB
IL tipico, connettore B	0,15 dB
RL minimal, connector A	35 dB
RL minimal, connector B	35 dB
RL typical, connector A	45 dB
RL typical, connector B	45 dB
Tipologia di fibra	G50/125 OM4

Proprietà meccaniche

Colore corpo connettore A	magenta
Colore corpo connettore B	magenta

Scope of delivery

HD-DCS Breakout cables (FR/LSOH) with 12-144 fibres OM4.
 High-performance connector assembly at either end with MTP Elite (male).
 Sticker labelling at both cable ends.
 Test reports on all MTP connectors.

Standards

MTP standard (IEC)	IEC 61754-7, IEC 61755-3-31, IEC 61755-3-32
Polarity standard	TIA-568-C.3 Type A,B,C
Zero halogen no corrosive gases	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2
Flame Propagation	EN 60332-1-2, IEC 60332-1-2, VDE 0482-332-1-2
Flame Spread	IEC 60332-3-24
Smoke Density	IEC 61034-1/-2, EN 61034-1/-2, VDE 0482-1034-1/-2

Nota

Insertion Loss (IL) is determined by the latest measurement methods under EFL multimode excitation conditions (EFL = Encircled Flux Launch) at 850 nm in accordance with IEC 61280-4-1.

Versions

Numero Materiale	Product	Outer sheath colour	Numero di fibre	Diametro esterno della guaina [mm]	Minimum bending radius	Tensile load short term [N]	Tensile load continuous [N]	Crush resistance short term [N]	Crush resistance continuous [N]	Number of connectors side A	Number of connectors side B	Number of fibres per connector A	Number of fibres per connector B	Peso [kg]	Packing unit
475000	HD-DCS Breakout cable 1x MTP - 1x MTP	heather violet	12	4,5	60	500	200	5.000	1.000	1	1	12	12	0,3 kg	al metro
475001	HD-DCS Breakout cable 2x MTP - 2x MTP	heather violet	24	6,6	90	600	400	5.000	1.000	2	2	12	12	0,3 kg	al metro
475002	HD-DCS Breakout cable 4x MTP - 4x MTP	heather violet	48	6,6	90	600	400	5.000	1.000	4	4	12	12	0,3 kg	al metro
475004	HD-DCS Breakout cable 8x MTP - 8x MTP	heather violet	96	9,2	130	1.000	800	5.000	1.000	8	8	12	12	0,3 kg	al metro
475005	HD-DCS Breakout cable 12x MTP - 12x MTP	heather violet	144	10,3	150	1.400	1.200	5.000	1.000	12	12	12	12	0,3 kg	al metro
475010	HD-DCS Breakout cable 1x MTP - 1x MTP	heather violet	12	4,5	60	500	200	5.000	1.000	1	1	12	12	0,3 kg	al metro
475011	HD-DCS Breakout cable 2x MTP - 2x MTP	heather violet	24	6,6	90	600	400	5.000	1.000	2	2	12	12	0,3 kg	al metro



Numero Materiale	Product	Outer sheath colour	Numero di fibre	Diametro esterno della guaina [mm]	Minimum bending radius	Tensile load short term [N]	Tensile load continuous [N]	Crush resistance short term [N]	Crush resistance continuous [N]	Number of connectors side A	Number of connectors side B	Number of fibres per connector A	Number of fibres per connector B	Peso [kg]	Packing unit
475012	HD-DCS Breakout cable 4x MTP - 4x MTP	heather violet	48	6,6	90	600	400	5.000	1.000	4	4	12	12	0,3 kg	al metro
475014	HD-DCS Breakout cable 8x MTP - 8x MTP	heather violet	96	9,2	130	1.000	800	5.000	1.000	8	8	12	12	0,3 kg	al metro
475015	HD-DCS Breakout cable 12x MTP - 12x MTP	heather violet	144	10,3	150	1.400	1.200	5.000	1.000	12	12	12	12	0,3 kg	al metro

MTP® and MTP Elite® are registered brands of US Conec.

Con riserva di modifiche tecniche

A partire da 2021-07-05 08:28:49