

## HD-DCS Fanout cables MTP-LCDU, 12 fibres OS2

for connecting active components



HD-DCS Fanout cables MTP-LCDU, 12 fibres OS2

### Description

Thin, very flexible fibre-optic fanout cable (round cable, Ø 2.0 mm) with 12 fibres.  
 Low fire load due to its halogen-free flame-retardant LS0H sheath.  
 Available with 2.5 m standard length (other lengths on request).  
 Standard connectivity method can be type A or type C.  
 Sticker labelling at both cable ends.  
 Breakout separation is effected with a thin divider housing.  
 The legs (Ø 2.0 mm) with LCD Uniboot (LCDU) plugs are numbered (1-6).  
 The legs can be ordered graded in length or of equal length.  
 Project-specific assemblies are available on request.

### Application

MTP-on-LCDU fanout cables are suitable for all high-performance applications in a data centre environment.  
 The connection between six duplex ports and one parallel optic port enables quick and space-saving cabling of active components such as routers, switches, servers and storage systems.  
 The fanout cables are assembled to a very high quality and guarantee optimum values for optical performance (IL/RL).

### Construction

Outer sheath colour	yellow
Outer sheath material	FR/LSZH

### Optical Properties

Colour code	IEC 60304
Connector gender side A	Female (unpinned)
Connector type side A	MTP
Connector type side B	LCDU
Ferrule polishing connector A	Elite APC 8°
Ferrule polishing connector B	PC 0°
Fibre type	E9/125 G.652.D BLO
IL maximal, connector A	0.3 dB
IL maximal, connector B	0.25 dB
IL typical, connector A	0.1 dB
IL typical, connector B	0.1 dB
RL minimal, connector A	65 dB
RL minimal, connector B	50 dB
RL typical, connector A	70 dB
RL typical, connector B	55 dB

## Mechanical properties

Housing colour connector A	yellow
Housing colour connector B	blue

## Scope of delivery

HD-DCS Fanout cables (FR/LSOH) with 12 fibres.  
 High-performance connector assembly with MTP Elite and LCD Uniboot Intelli-Cross Pro.  
 All connectors incl. push-pull tabs.  
 Sticker labelling at both cable ends.  
 Test reports (IL/RL) on all connectors.

## Standards

LC standard (IEC)	IEC 61754-20
MTP standard (IEC)	IEC 61754-7, IEC 61755-3-31, IEC 61755-3-32
Polarity standard	TIA-568-C.3 Type A,B,C
Zero halogen no corrosive gases	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2
Flame Propagation	IEC 60332-1-2, EN 60332-1-2, VDE 0482-332-1-2
Flame Spread	IEC 60332-3-24
Smoke Density	IEC 61034-1/-2, EN 61034-1/-2, VDE 0482-1034-1/-2

## Versions

Material number	Product	Outer sheath colour	Number of Fibres	Outer sheath diameter [mm]	Minimum bending radius	Tensile load short term [N]	Tensile load continuous [N]	Crush resistance short term [N]	Crush resistance continuous [N]	Length (m)	Polarity	Number of connectors side A	Number of connectors side B	Number of fibres per connector A	Number of fibres per connector B	Gradation	Weight [kg]	Packing unit	Whip type
473720	HD-DCS Fanout cable 1x MTP - 6x LCDU, equal length	yellow	12	2.0	40	500	200	1,000	100	2.5	A	1	6	12	2	equal length	0.14 kg	1 pc.	equal length
473721	HD-DCS Fanout cable 1x MTP - 6x LCDU, graded length	yellow	12	2.0	40	500	200	1,000	100	2.5	A	1	6	12	2	graded length	0.14 kg	1 pc.	staggered length
473725	HD-DCS Fanout cable 1x MTP - 6x LCDU, equal length	yellow	12	2.0	40	500	200	1,000	100	2.5	C	1	6	12	2	equal length	0.14 kg	1 pc.	equal length
473726	HD-DCS Fanout cable 1x MTP - 6x LCDU, graded length	yellow	12	2.0	40	500	200	1,000	100	2.5	C	1	6	12	2	graded length	0.14 kg	1 pc.	staggered length

MTP® and MTP Elite® are registered brands of US Conec.

