

## FO-DCS 3U/7HP BO plug-in-modules, 6x LCQ

for FO-DCS modular subracks / panels, OM4



High-Performance FO-DCS BO plug-in modules LCD, 3U/7HP

### Description

Open polycarbonate housing (PC) and front panel 3U / 7HP in polycarbonate (black).  
 The radius limiter on the rear side and the integrated clips ensure a simple and safe handling of the pre-assembled legs.  
 The front panel is fitted with 6 LCD adapters and provides two integrated labelling strips on both sides of the LCD ports for customer-specific printing.  
 Fixation with two knurled screws (captive).

### Applicazione

FO-DCS breakout plug-in modules LCQ (24F 3U/7HP) are suitable for all high-performance applications with duplex signals, particularly in the data centre environment.  
 They find modular application in FO-DCS modular panels (19"/1U) or in FO-DCS subracks (19"/3U, 19"/4U).  
 They are used to accept pre-assembled LC/LCD trunk cables.  
 Packing densities of up to 144 fibres on 3U are achieved with these plug-in modules.

### Proprietà generali

Acceptance capacity	6 quad ports (24 fibres)
Fully equipped	Yes

### Proprietà ottiche

Adapter colour, front side	heather violet
Adapter material, front side	Polimerico
Adattatore, lato anteriore	6 x LCQ, heather violet (Dust plug)
Materiale manicotto, lato anteriore	Zirconia (ZrO <sub>2</sub> )
Number of adapters, front side	6
Tipo di adattatore, lato anteriore	LCQ
Tipologia di fibra	OM4

## Proprietà meccaniche

Dust protection, frontside	Yes
Dust/Laser protection, frontside	Dust plug
Laser protection, frontside	No

## Scope of delivery

Housing with front panel, equipped with 6 LC duplex adapters (ceramic sleeves).  
All ports are fitted with two transparent dust protection plugs (front/rear).  
Rear side with integrated radius limiter and clips for the pre-assembled legs.  
Optional LCD laser protection clips (metal) can be obtained and retrofitted.

## Nota

As a high-performance patch cable we recommend the FO-DCS LCD Uniboot patch cables.

## Versions

Numero Materiale	Product	Dimensioni esterne	Colore	Materiale	Peso [kg]	Packing unit
571571	FO-DCS BO plug-in-module LCQ 3U/7HP, 6x LCQ, magenta	3 U, 129 mm x 35 mm x 182 mm	nera	Polycarbonate (PC)	0,15 kg	1 pc.

Con riserva di modifiche tecniche

A partire da 2021-07-05 08:28:47