

## Breakout box OV-S

19"/1 U, OM5, LCD/PC

with adapters



### Description

For the termination of pre-assembled fibre optic cables.  
Loaded with a maximum of 12 / 24 FO adapters.

### General properties

Outer dimensions (HxWxD)	1 U, 42 mm x 482.2 mm x 245 mm
Housing	metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm)
Front plate	similar to RAL 7035, similar to RAL 9005 or stainless steel
Imprint	numbers (silk screen printing) on frontplate
Cable entry	rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary
Strain relief	with cable tie and screwed cable gland (M20)
Capacity	up to 48 fibres
Labelling strip included	no
Mounting set included	no
Extractable drawer	yes
Fold-down drawer	no

### Optical Properties

Fibre class	Multimode
Fibre category	OM5
Adapter	LCD/PC
Adapter colour	lime green

### Scope of delivery

Breakout box with  
- two straight cable entries  
- FO adapters, fastened by screws

### Versions

Material number	Product	Colour (Frontplate)	Number of adapters	Adapter orientation	Weight [kg]	Packing unit	GTIN / EAN
41513300ZY	Breakout box OV-S 6xLCD/PC	light grey	6	offset horizontal	2.7 kg	1 pc.	40393910013962
41513400ZY	Breakout box OV-S 6xLCD/PC	black	6	offset horizontal	2.7 kg	1 pc.	40393910013948
41513500ZY	Breakout box OV-S 12xLCD/PC	light grey	12	offset horizontal	2.7 kg	1 pc.	40393910013924
41513600ZY	Breakout box OV-S 12xLCD/PC	black	12	offset horizontal	2.7 kg	1 pc.	40393910013900
41513700ZY	Breakout box OV-S 24xLCD/PC	light grey	24	offset horizontal	2.7 kg	1 pc.	40393910013887
41513800ZY	Breakout box OV-S 24xLCD/PC	black	24	offset horizontal	2.7 kg	1 pc.	40393910013863

Variants on request.



Subject to technical modification

As of 2023-02-07 14:15:54