

Breakout box OV-S

19"/1 U, OS2, LSH/APC

with adapters



Description

For the termination of pre-assembled fibre optic cables.
Loaded with a maximum of 12 / 24 FO adapters.

General properties

Outer dimensions (HxWxD)	1 U, 42 mm x 482.2 mm x 245 mm
Housing	metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm)
Front plate	similar to RAL 7035, similar to RAL 9005 or stainless steel
Imprint	numbers (silk screen printing) on frontplate
Cable entry	rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary
Strain relief	with cable tie and screwed cable gland (M20)
Capacity	up to 24 fibres
Labelling strip included	no
Mounting set included	no
Extractable drawer	yes
Fold-down drawer	no

Optical Properties

Fibre class	Singlemode
Fibre category	OS2
Adapter	LSH/APC
Adapter colour	green

Scope of delivery

Breakout box with
 - two straight cable entries
 - FO adapters, fastened by screws

Versions

Material number	Product	Colour (Frontplate)	Number of adapters	Adapter orientation	Weight [kg]	Packing unit	GTIN / EAN
41531900ZY	Breakout box OV-S 6xLSH/APC	light grey	6	vertical	2.3 kg	1 pc.	40393910011531
41532100ZY	Breakout box OV-S 12xLSH/APC	light grey	12	vertical	2.6 kg	1 pc.	40393910011487
41532300ZY	Breakout box OV-S 24xLSH/APC	light grey	24	vertical	2.7 kg	1 pc.	40393910011432

Variants on request.



Subject to technical modification

As of 2023-02-07 14:15:54