

Breakout box OV-S

19"/1 U, OM3, LCD/PC

with adapters, labelling strip and mounting set



Description

For the termination of pre-assembled fibre optic cables.
Loaded with a maximum of 12 / 24 FO adapters.

General properties

Outer dimensions (HxWxD)	1 U, 42 mm x 482.2 mm x 245 mm
Housing	metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm)
Front plate	similar to RAL 7035, similar to RAL 9005 or stainless steel
Imprint	numbers (silk screen printing) on frontplate
Cable entry	rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary
Strain relief	with cable tie and screwed cable gland (M20)
Capacity	up to 48 fibres
Labelling strip included	yes
Mounting set included	yes
Extractable drawer	yes
Fold-down drawer	no

Optical Properties

Fibre class	Multimode
Fibre category	OM3
Adapter	LCD/PC
Adapter colour	turquoise

Scope of delivery

- Breakout box with
- two straight cable entries
 - FO adapters, fastened by screws
 - labelling strip
 - mounting set

Versions

Material number	Product	Colour (Frontplate)	Number of adapters	Adapter orientation	Weight [kg]	Packing unit	GTIN / EAN
41542601ZY	Breakout box OV-S 6xLCD/PC	black	6	offset horizontal	2.6 kg	1 pc.	40393910010206
41525201ZY	Breakout box OV-S 6xLCD/PC	light grey	6	offset horizontal	2.6 kg	1 pc.	40393910012538
41542801ZY	Breakout box OV-S 12xLCD/PC	black	12	offset horizontal	2.6 kg	1 pc.	40393910010169
41525601ZY	Breakout box OV-S 12xLCD/PC	light grey	12	offset horizontal	2.6 kg	1 pc.	40393910012422
41543001ZY	Breakout box OV-S 24xLCD/PC	black	24	offset horizontal	2.6 kg	1 pc.	40393910010121
41526001ZY	Breakout box OV-S 24xLCD/PC	light grey	24	offset horizontal	2.6 kg	1 pc.	40393910012316

Variants on request.



Subject to technical modification

As of 2023-02-07 14:15:54