

Splice box OV-S

19"/1 U, E9/125 G.652.D BLO OS2, ST/PC

with adapters and pigtails



Description

For the termination of fibre optic cables.

Loaded with FO adapters, ready for splicing, with prepared pigtails (per 2 m, colour code: IEC 60304).

General properties

| | |
|----------------------------|--|
| Outer dimensions (HxWxD) | 1 U, 42 mm x 482.2 mm x 245 mm |
| Housing | metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm) |
| Front plate | similar to RAL 7035, similar to RAL 9005 or stainless steel |
| Imprint | numbers (silk screen printing) on frontplate |
| Cable entry | rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary |
| Strain relief | with cable tie and screwed cable gland (M20) |
| Capacity | up to 24 fibres |
| Labelling strip included | no |
| Mounting set included | no |
| Splice protectors included | no |
| Extractable drawer | yes |
| Fold-down drawer | no |

Optical Properties

| | |
|------------------------------|--------------------|
| Fibre class | Singlemode |
| Fibre type | E9/125 G.652.D BLO |
| Fibre category | OS2 |
| Colour code | IEC 60304 |
| Adapter | ST/PC |
| Adapter colour | silver |
| Ferrule material | Zirconia |
| Insertion loss (IL), maximal | 0.25 dB |
| Insertion loss (IL), typical | 0.12 dB |
| Return loss (RL), minimal | 50 dB |
| Return loss (RL), typical | 55 dB |

Scope of delivery

- Splice box with
- two straight cable entries
- one screwed cable gland M20
- coloured pigtails with measurement report
- FO adapters, fastened by screws
- splice trays with cover
- splice holder for 12 x crimp splice protectors

Versions

| Material number | Product | Colour (Frontplate) | Number of adapters | Adapter orientation | Pigtails | Weight [kg] | Packing unit | GTIN / EAN |
|-----------------|-----------------------------|---------------------|--------------------|---------------------|----------|-------------|--------------|----------------|
| 41534400ZY | Splice box OV-S 6xST/PC | black | 6 | vertical | 6 x ST | 2.8 kg | 1 pc. | 40393910011142 |
| 41523400ZY | Splice box OV-S 6xST/PC | light grey | 6 | vertical | 6 x ST | 2.8 kg | 1 pc. | 40393910012774 |
| 41535100ZY | Splice box OV-S 12xST/PC | black | 12 | vertical | 12 x ST | 2.5 kg | 1 pc. | 40393910011111 |
| 41523800ZY | Splice box OV-S 12xST/PC | light grey | 12 | vertical | 12 x ST | 2.5 kg | 1 pc. | 40393910012712 |
| 41535400ZY | Splice box OV-S 24xST/PC | black | 24 | vertical | 24 x ST | 2.5 kg | 1 pc. | 40393910011081 |
| 41524200ZY | Splice box OV-S 24xST/PC | light grey | 24 | vertical | 24 x ST | 2.5 kg | 1 pc. | 40393910012651 |

Variants on request.

