

## HD-DCS BO module, 12x MPO

for HD-DCS modular panels



### Descrizione

Polycarbonate (PC) housing with press-fit cover.  
At the rear the HD-DCS BO modules have two slots fitted with cable grommets.  
Front couplers with translucent dust plugs.

### Applicazione

HD-DCS BO modules are suitable for all high-density and high-performance applications with parallel optic signals, particularly in the data centre environment.  
They find modular application in the slots of the HD-DCS modular panels (19"/1U) in which they can be inserted from the front and the back.  
They are used to accept pre-assembled MTP trunk cables.  
A packing density of 576 fibres (MTP<sub>12</sub>) on 1U are achieved with these type of modules.

### Proprietà generali

Acceptance capacity	144 fibres (MTP <sub>12</sub> )
---------------------	---------------------------------

### Proprietà ottiche

Adapter colour, front side	nero
Adapter material, front side	Polimerico
Adattatore, lato anteriore	2 x 6MPO, nero (Dust plug)
Number of adapters, front side	2
Tipo di adattatore, lato anteriore	6MPO

### Proprietà meccaniche

Dust protection, frontside	Yes
Dust/Laser protection, frontside	Dust plug
Laser protection, frontside	No

### Ambito di consegna

Housing, equipped with 2x 6MPO adapter with translucent dust plug protection on front side.  
Rear side is fitted with a cable grommet.

### Standards

MTP standard (IEC)	IEC 61754-7, IEC 61755-3-31, IEC 61755-3-32
--------------------	---

## Nota

As high-performance patch cables for high-density solutions Datwyler recommends the HD-DCS MTP patch cables with push-pull rods.

## Versioni

Codice art.	Prodotto	Dimensioni esterne	Colore	Materiale	Unità di imballaggio	GTIN / EAN
473576	HD-DCS BO module, 12x MPO	39 mm x 100 mm x 120 mm	nero	Polycarbonate (PC)	1 pc.	40393910215076

MTP® and MTP Elite® are registered brands of US Conec.

Con riserva di modifiche tecniche

A partire da 2023-01-11 15:16:39