

HD-DCS BO module, 12x MPO

for HD-DCS modular panels



Beschrijving

Polycarbonate (PC) housing with press-fit cover.
At the rear the HD-DCS BO modules have two slots fitted with cable grommets.
Front couplers with translucent dust plugs.

Toepassing

HD-DCS BO modules are suitable for all high-density and high-performance applications with parallel optic signals, particularly in the data centre environment.
They find modular application in the slots of the HD-DCS modular panels (19"/1U) in which they can be inserted from the front and the back.
They are used to accept pre-assembled MTP trunk cables.
A packing density of 576 fibres (MTP₁₂) on 1U are achieved with these type of modules.

Algemene eigenschappen

Acceptatie capaciteit	144 vezels (MTP ₁₂)
-----------------------	---------------------------------

Optische eigenschappen

Aantal adapters, voorzijde	2
Adapter, voorkant	2 x 6MPO, zwart (Dust plug)
Adapter colour, front side	zwart
Adapter material, front side	Polymerisch
Type adapter, voorkant	6MPO

Mechanische eigenschappen

Laserbescherming, voorzijde	No
Stof- / laserbescherming, voorzijde	Dust plug
Stofbescherming, voorzijde	Yes

Leveringsomvang

Housing, equipped with 2x 6MPO adapter with translucent dust plug protection on front side.
Rear side is fitted with a cable grommet.

Normen / Standards

MTP standard (IEC)	IEC 61754-7, IEC 61755-3-31, IEC 61755-3-32
--------------------	---

Noot

As high-performance patch cables for high-density solutions Datwyler recommends the HD-DCS MTP patch cables with push-pull rods.

Versies

Materiaalnummer	Artikel	Buitenste afmetingen	Kleur	Materiaal	Verpakkingseenheid	GTIN / EAN
473576	HD-DCS BO module, 12x MPO	39 mm x 100 mm x 120 mm	zwart	Polycarbonaat (PC)	1 stk.	40393910215076

MTP® and MTP Elite® are registered brands of US Conec.