

Splice box OV-S

19"/1 U, Singlemode , SCD/PC

with adapters



Description

For the termination of fibre optic cables.
Loaded with FO adapters, ready for splicing.

General properties

Outer dimensions (HxWxD)	1 U, 42 mm x 482.2 mm x 245 mm
Housing	metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm)
Front plate	similar to RAL 9005
Imprint	numbers (silk screen printing) on frontplate
Cable entry	rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary
Strain relief	with cable tie and screwed cable gland (M20)
Capacity	up to 48 fibres
Labelling strip included	yes
Mounting set included	no
Splice protectors included	no

Optical Properties

Fibre class	Singlemode
Adapter	SCD/PC
Adapter colour	blue

Scope of delivery

- Splice box with
- two straight cable entries
 - one screwed cable gland M20
 - FO adapters
 - splice trays with cover
 - splice holder for 6 x shrink splice protectors in required quantity
 - labelling strip, 410 mm

Versions

Material number	Product	Colour (Frontplate)	Number of adapters	Adapter orientation	Laser protection	Weight [kg]	Packing unit	GTIN / EAN
41538804ZY	Splice box OV-S 24xSCD/PC	black	24	vertical	No	3 kg	1 pc.	40393910215113

Variants on request.



Subject to technical modification

As of 2023-02-06 13:16:03